



FTC Series Rotary Tillers

36, 40, and 48 Inch Rotary Tillers

Perfect for Sub-Compact Tractors up to 25 HP



The FTC Series provides the perfectly designed rotary tillers for serious gardeners and those operating sub-compact and compact tractors. These well-built tillers guarantee dependable service and top notch results year after year.

Standard Features Include:

- Six tines per flange on FTC 48, four tines per flange on FTC 36 and 40
- Drive Housing Oil Level Sight Glass for Ease of Maintenance
- Heavy Duty Zinc Plated Jack Stand
- Shear bolt PTO

Options Include:

- Slip Clutch PTO

Specifications	FTC 36	FTC 40	FTC 48
Working Width (Inches)	36	40	48
Working Depth (Inches)	4.75	4.75	4.75
Blades per Flange	4	4	6
Total Blades	16	20	36
Transmission Type	Chain	Chain	Chain
Driveline Protection	Shear Bolt	Shear Bolt	Shear Bolt
Optional Driveline Protection	Slip Clutch	Slip Clutch	Slip Clutch
Hitch	Cat. I	Cat. I	Cat. I
PTO Power Recommended (HP)	13-17	15-20	20-25
Optimum PTO Speed (RPM)	540	540	540
Rotor Tube Diameter (Inches)	2	2	2
Aproximate Weight (LBS)	253	275	297



For more information contact:
 Unifarm Machinery Corporation PO Box 38 (27894) 4608 Lely Road, Wilson, NC 27893
 Phone: 252-291-3997 Fax: 252-291-7354 Toll Free: 877-294-3997
 Email: sales@unifarm.biz Website: www.unifarmmachinery.com