



T4 Series Rotary Tillers

40, 48, and 59 Inch Rotary Tillers

Quality and Performance at an Affordable Price



The Phoenix T4 family of rotary tillers are perfect for the independent week end gardner or horticultural enthusiast that likes to do things for themselves. No worries about these tillers, they are built for dependable trouble free performance year after year.

Standard Features Include:

- 6 Tines Per Flange
- Two Position and Adjustable/Off Setable Lower Hitch Blocks (for up to 4" of offset)
- Adjustable Skids
- Heavy Duty Castings and Bearings with Double Lip Seals.
- Powder Coat Paint Finish Available in Red Or Orange
- Heavy Duty Adjustable Drag Board With Zinc Plated Check Chain
- Standard Eurocardan Series 4 PTO Shaft With Slip Clutch

Specifications	T4 400S	T4 48	T4-59
Working Width (Inches)	40	48	59
Working Depth (Inches)	7	7	7
Blades per Flange	6	6	6
Scroll Diameter (Inches)	15.7	15.7	15.7
Total Blades	24	30	36
Rotor Flange Thickness	3/8	3/8	3/8
Rotor Speed (RPM)	250	250	250
Drive Chain	#60	#60	#60
Driveline Protection	Slip Clutch	Slip Clutch	Slip Clutch
Hitch	Cat I	Cat I	Cat I
PTO Shaft Series	4	4	4
PTO Power Required (HP)	15-25	15-25	15-25
Optimum PTO Speed (RPM)	540	540	540
Aproximate Weight (LBS)	308	335	360



For more information, contact:
 Uniform Machinery Corporation PO Box 38 (27894) 4608 Lely Road, Wilson, NC 27893
 Phone: 252-291-3997 Fax: 252-291-7354 Toll Free: 877-294-3997
 Email: sales@unifarm.biz Web Site: www.unifarm.biz

Specifications	T4-400S	T4-48	T4-59
Working Width (Inches)	40	48	59
Working Depth (Inches)	7	7	7
Blades per Flange	6	6	6
Scroll Diameter (Inches)	15.7	15.7	15.7
Total Blades	24	30	36
Rotor Flange Thickness	3/8	3/8	3/8
Rotor Speed (RPM)	250	250	250
Drive Chain	#60	#60	#60
Driveline Protection	Slip Clutch	Slip Clutch	Slip Clutch
Hitch	Cat I	Cat I	Cat I
PTO Shaft Series	4	4	4
PTO Power Required (HP)	15-25	15-25	15-25
Optimum PTO Speed (RPM)	540	540	540
Aproximate Weight (LBS)	308	335	360